Dimplex®

Revillusion™

36" Built-in Electric Firebox

RBF36



Revillusion[™] is a completely new way of looking at fireplaces, and changing the standard for electric. A clear view through the lifelike flames, to the full brick interior, captures the charm of a wood-burning fireplace. Enjoy the look of a fireplace cut straight from the pages of a magazine by choosing Revillusion[™]; clearly a better fireplace.







Revillusion™

36" Built-in Electric Firebox

RBF36



Accessories



36" Single Glass Pane, tamperproof glass (RBFGLASS36)

120 V | 1,375 W | 4,400 BTU 208 V | 1,975 W | 6,745 BTU 240 V | 2,575 W | 8,794 BTU

Mood-maker Remote Customize the light color and intensity for a fireplace that reflects your personality.



Model #	Description	Lbs / Kg	UPC	Wty*	Carton Dimensions (WxHxD)		Cube	
					Inches	cm	ft³	m³
RBF36	36" Built-in Electric Firebox	74.9 / 34.0	781052 104723	2 yrs.	41-1/4 x 15-1/4 x 31-7/8	104.6 x 38.7 x 81.0	11.6	0.3
RBFGLASS36	Single Glass Pane	25.1 / 11.4	781052 108011	1 yr.	42-1/4 x 29-1/4 x 4-1/4	106.8 x 74.2 x 10.6	3.0	0.08
RBFPLUG	Plug Kit		781052 107656					

Specifications, finishes and dimensions are subject to change. †Limited warranty. ©2017 Dimplex North America Limited.

Features

Revillusion™ Flame Technology Flames are larger, brighter and more random, appearing from within the logs.

Mirage™ Flame Panel
Partially frosted acrylic panel is clearly better than a mirror, showing only dazzling flames and no reflections.

ThruView™ Full-depth Design See clear through the flames to the back of the firebox for a more authentic experience.

Mood Lighting
Customize the firebox glow with a choice of warm hues, plus midnight mode.

Color Enhancement
Adjust the flame base color to red or blue.

EXECUTE: Realogs™ Plus

A full grate of life-size hardwood-cast logs, tiered for greater depth.

Full Brick-surround Firebox
More authentic day or night;
270-degree herringbone brick
with natural soot markings.

Adjust light level to suit the room and choose flicker effect for enhanced firelight.

Ambient Light Sensor
Automatically adjusts firebox light to suit the room day to night.

Quick and Easy Installation Simply frame, wire and finish – no venting, gas lines or safety screens.

Primary Heat
Option to use 240 volt supply for up
to 8,800 BTU - use as part of primary
heating plan; heater also operates
without flame and can be deactivated.

All-season Flames
Enjoy the unique charm of a fireplace
365 days a year using the flames
without the heat.

Direct-wire
Designed to be direct-wired to a 120, 208 or 240 volt circuit for a seamless look (optional plug kit available).

Low Carbon Footprint
The most sustainable fireplace option; no emissions and 100% efficient.

SE-029-R05-022217





Revillusion™

36" Built-in Electric Firebox

RBF36

Product Dimensions:





