



SPECIFICATIONS

	GEOLOGY	Limestone
	TYPE	100% Splitface
	PATTERN	Natural Coursed Heights; 2:1 Random Ashlar
	HEIGHTS	2" - 8"
	LENGTHS	Thin Veneer: 6" - 20" (Crated or palletized material can exceed 20")
	DEPTHS	Thin Veneer: .75" - 1.25" Full Veneer: 3" - 5"
	COLORS	Muted grays, blues, beige/buff hues.
	COVERAGE	35 - 40 Sq Ft per Ton
	WEIGHT	~13.6 lbs per Sq Ft (Thin Veneer)
	FLATS	10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 200 s/f Pallet
	CORNERS	10 Ln Ft per Box; 100 Ln Ft per Crate; 100 Ln Ft per Pallet
	NOTES	NEW (Tumbled: Pre-packaged blend of 1/3 Columbia , 1/3 Florence , 1/3 Lucca)

ASTM C-97

Water Absorption %	.41
Bulk Specific Gravity	2.81

ASTM C-170

Parallel to Rift, Dry (psi)	28700
Parallel to Rift, Wet (psi)	26150
Perpendicular to Rift, Dry (psi)	32600
Perpendicular to Rift, Wet (psi)	29550

ASTM C-99

Parallel to Rift, Dry (psi)	2905
Parallel to Rift, Wet (psi)	2595

ASTM C-880

Perpendicular to Rift, Dry (psi)	
Perpendicular to Rift, Wet (psi)	

