



## SPECIFICATIONS

|                                                                                    |                 |                                                                                                 |
|------------------------------------------------------------------------------------|-----------------|-------------------------------------------------------------------------------------------------|
|  | <b>GEOLOGY</b>  | Limestone                                                                                       |
|  | <b>TYPE</b>     | 100% Bedface                                                                                    |
|  | <b>PATTERN</b>  | Sawn Course Heights   2:1 Dimensional Ashlar                                                    |
|  | <b>HEIGHTS</b>  | 2.25", 5", 7.75"                                                                                |
|  | <b>LENGTHS</b>  | Full Veneer: 8" - 48"   Thin Veneer: 6" - 20"<br>(Crated or Palletized Material can exceed 20") |
|  | <b>DEPTHS</b>   | Thin Veneer: .75" - 1.25"   Full Veneer: 3" - 5"                                                |
|  | <b>COLORS</b>   | Muted beige, buff, grays                                                                        |
|  | <b>COVERAGE</b> | 35 - 40 Sq Ft per Ton (Full Veneer)                                                             |
|  | <b>WEIGHT</b>   | ~13.7 lbs per Sq Ft (Thin Veneer)                                                               |
|  | <b>FLATS</b>    | 10 s/f Box; 100 s/f Crate, 180 s/f Crate; 100 s/f Pallet, 200 s/f Pallet                        |
|  | <b>CORNERS</b>  | Ln/Ft Box; 100 Ln/Ft Crate; 100 Ln/Ft Pallet                                                    |
|  | <b>NOTES</b>    | <b>NEW</b> (Tumbled version of "Heritage Dimensional")                                          |

### ASTM C-97

|                       |      |
|-----------------------|------|
| Water Absorption %    | .31  |
| Bulk Specific Gravity | 2.83 |

### ASTM C-170

|                                  |       |
|----------------------------------|-------|
| Parallel to Rift, Dry (psi)      | 36100 |
| Parallel to Rift, Wet (psi)      | 32000 |
| Perpendicular to Rift, Dry (psi) | 35800 |
| Perpendicular to Rift, Wet (psi) | 30000 |

### ASTM C-99

|                             |      |
|-----------------------------|------|
| Parallel to Rift, Dry (psi) | 3770 |
| Parallel to Rift, Wet (psi) | 3500 |

### ASTM C-880

|                                  |      |
|----------------------------------|------|
| Perpendicular to Rift, Dry (psi) | 1780 |
| Perpendicular to Rift, Wet (psi) | 1730 |

